Create Low Fog With Our Advanced LSX Fog Converter





The LSX is an advancement in low fog technology, using proven high performance refrigeration components to create a powerful cooling unit. The LSX is designed to chill fog between 5 to 25 degrees Fahrenheit (-15 to -4 degrees Celsius) without the use of liquid CO₂. It creates light, wispy low-lying fog effects efficiently and effectively.

The overall smaller size, integrated carry handles and heavy duty caster wheels make handling and setup easy. When paired with Ultratec's Premier Fog Generator, the LSX uses continuous output to push low-lying fog via a built-in adjustable fan, transforming your stage or set in moments.

The LSX creates low fog effects for live theatre and concert events, setting the stage for exciting entrances and dramatic moments. It is particularly ideal when liquid CO2 is not readily available for creating low fog.





| MODELS | | |
|----------|-----------------------------------|--|
| CLF-2930 | LSX MKII Low Smoke Converter 110v | |
| CLF-2915 | LSX MKII Low Smoke Converter 220v | |

| ACCESSORIES | |
|-------------|-------------------------------|
| CLF-2936 | LSX 8" Uninsulated Hose - 25' |

| SPECIFICATION | ECIFICATIONS | | |
|---------------------------|--|--|--|
| Length: | 30 in / 76.2 cm | | |
| Width: | 26 in / 66.04 cm | | |
| Height: | 28 in / 71 cm | | |
| Net Weight: | 150 lbs / 68 kgs | | |
| Power Cord: | 6 ft - 1.8 m interconnect cord | | |
| Rating: | 12 amps @ 110 volts @ 60 hz | | |
| Regulatory Compliance: | This product has been certified to CSA/UL Standards by QPS Canada Inc. | | |

Specifications: Note specifications are based on the LSX Only

WARRANTY

The LSX has a five-year warranty against manufacturer's defect provided Ultratec fluids are used.

Visit www.ultratecfx.com for a complete set of specifications on all models.







