Create Intense Fog Effects With the Fog Burst and Mega Fog Burst

ultratec special effects®

Ultratec's Power Fog Industrial 9D Fog Burst and G3000 Mega Burst can be used individually, or in tandem set-ups to create instant fog effects. Designed for ease-of-use, both fog generators come standard 5-pin DMX control or manual control. An optional CO^2 regulator with 5' hose is available.

Built with our 1400-watt Heat Exchanger, the Power Fog Industrial can be rotated 90 degrees to stand upright offering flexibility for show designs. Rubber feet and plastic glides offer the utmost stability. The G3000 Mega Fog Burst uses our 2000-watt dual core block has optional stands for show designs and applications.

Quick Dissipating Fluid is great for effects that require fog to dissipate quickly. Extra Quick Dissipating Fluid dissipates twice as fast (not pictured). Using our fluids maintains your five-year warranty against manufacturer's defect.

MADE IN NORTH AMERICA · ULTRATEC FX · SINCE 1992

ultratecfx.com

SETTING THE STANDARD IN SPECIAL EFFECTS FOR OVER 25 YEARS

ultratec special effects®

Built in 5-Pin DMX control or manual control via backlit digital interface

CO^2 Regulator w/5' Hose (optional for the mega fog burst or fog burst)

Mega Fog Burst adjustable stand

Built in 5-Pin DMX control

Terminal Strip Connection for Show Control (Dry Contacts)

Optional Fluid Container Holder

MEGA FOG BURST MODELS (G3000 NOT INCLUDED)	
CLF-4475	G3000 Mega Fog Burst 110V
CLF-4477	G3000 Mega Fog Burst 220V

MEGA FOG BURST AIR REQUIREMENTS IN SCFM	
Pressure	Mega Fog Burst
20 PSI	16
40 PSI	23
60 PSI	30
80 PSI	37
90 PSI	40
100 PSI	44

The Mega Fog Burst gives 17 times output or about 750 CFM @ 100 PSI

FOG BURST MODEL (PFI 9D NOT INCLUDED)	
CLF-4455	Fog Burst for PFI/PFI 9D 110V

FOG BURST AIR REQUIREMENTS IN SCFM	
Pressure	Fog Burst
20 PSI	8
40 PSI	11
60 PSI	15
80 PSI	19
90 PSI	22
100 PSI	25

The Fog Burst gives 15 times output or about 375 CFM @ 100 PSI

WARRANTY

The Fog Burst and Mega Fog Burst have a five-year warranty against manufacturer's defect provided Ultratec fluids are used.

Visit www.ultratecfx.com to see available accessories, parts and for a complete set of specifications on all models.

ultratecfx.com
Canada - USA - Germany
Phone: 519-659-7972 / Toll Free: 800-388-0617 Email: sales@ultratecfx.com